

DH-PFA1330S

Plastic Junction Box



- Built of PC material that has a V2 flame-retardant grade and is cost-effective.
- Quick mount structure allows for fast installation and removal.
- Side-press design allows for easy opening and closing.
- Includes knockout holes on the side and bottom that can be opened to function as outlets.



Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Humidity	10%–90% (RH)
Anti-corrosion Level	Basic Protection *The products are designed for general use and are applicable even in areas with no specific requirements for anti-corrosion protection.

Series Overview

The Junction Box is beautifully designed and highly convenient. Cables can be organized in it and there are outlets at the bottom and side of the box, making it easy to install and use.

Scene

Ideal for mounting cameras, and works in temperatures ranging from -40 °C to +60 °C (-40 °F to +140 °F) and in environments with a relative humidity of less than 90%.

Technical Specification

Structure	
Casing Material	PC
Product Dimensions	132.0 mm × 132.0 mm × 66.1 mm (5.20" × 5.20" × 2.60") (L × W × H)
Appearance Color	White
Net Weight	0.24 kg (0.53 lb)
Gross Weight	0.28 kg (0.62 lb)
Load Bearing	2.0 kg (4.41 lb)
Installation	Junction mount
Applicable Model	Please see Camera Accessories Selection
Environment	
Protection	IP55
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	<90% (RH)

Ordering Information

Type	Model	Description
Camera Mount	DH-PFA1330S	Plastic Junction Box

Installation



